BULLETIN

PRODUCT SPECIFICATIONS

7029 Journeyman FLEX Harness, Steel

Journeyman FLEX Steel, Climbing, Cross-Over, Non-Belted

The Journeyman FLEX Steel continues the tradition of uncompromising performance you've come to rely on every day. New design elements have been incorporated into this jobsite workhorse for improved comfort, durability and reliability. The Journeyman FLEX Steel continues the tradition of keeping your team safe.

Features

- · Aluminum hardware for lighter weight
- Four D-rings; One Back, Two Hip and One Sternal
- Quick Connect Visi-lock chest buckle
- 18" countoured leg pads
- · Friction torso adjusters
- · Tongue buckle Leg Adjusters
- · Non-slip dorsal D-ring adjustment

MATERIALS SPECIFICATIONS		
Webbing:	Polyester; Min. 5,000 lbs. tensile strength	
Keepers:	Plastic	
D-Rings:	Steel; Min. 5,000 lbs. tensile strength	
Buckles/Adjusters:	Steel; Min. 3,375 lbs. tensile strength	
Grommets:	Brass	
Torsos Adjusters:	Friction	
Foam:	High density internal foam	

PERFORMANCE SPECIFICATIONS		
Maximum Working Load:	425 lbs.	
ANSI User Capacity:	130 to 310 lbs. Max.	
OSHA User Capacity:	130 to 425 lbs. Max.	

SIZES		
Style #	Description	
PN 7029XS	X Small	
PN 7029	UniFit	
PN 7029XL	X Large	
PN 70292X	2X Large	
PN 70293X	3X Large	
For shoulder and waist size ranges, please see Size Charts page.		



Journeyman FLEX Harness, Steell

RELEVANT STANDARDS		
ANSI:	Z359.11-2014	
OSHA:	1926.502, 1910.66	

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a shock absorbing lanyard to a side D-Ring.

