

PRODUCT SPECIFICATIONS



727620

Contractor Class 1 SRL with 20' Galvanized Cable and Anchorage Carabiner

Features :

- 3/16" galvanized steel cable lifeline with load-indicating swivel snap hook
- Features glass-filled nylon housing for durable impact resistance.
- Lifeline includes recoil spring bumper to reduce retraction lock-up
- Rugged internal steel drum and inertial braking system deliver reliable performance
- SRL includes double-locking twist-lock anchorage carabiner
- Complies with ANSI Z359.14-2021 Class 1 SRL. [Learn more and download White Paper](#)



Material Specifications		Performance Specifications		Compliant With:	
Cable	3/16" galvanized steel; 3,600 lb min. static strength	Static Strength	3,600 lb min.	ANSI	Z359.14-2021
Lifeline Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength	ANSI SRL Class/Type	Class 1 SRL	OSHA	1926.502 and 1910.66
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength	Avg. Arrest Force	900 lb		
		Max. Arrest Force	1,800 lb		
		Max. Arrest Distance	42"		
		ANSI User Capacity	130 to 310 lb max.		
		OSHA User Capacity	130 to 310 lb max.		

Sizes & Part Numbers						
727620 -20' (ANSI Compliant)	727630C - 30' (ANSI Compliant)	C727630 - 30' (CSA Compliant)	727650C - 50' (ANSI Compliant)	C727650 - 50' (CSA Compliant)	7276100 - 100' (ANSI Compliant)	

1306 S. Alameda St., Compton, CA 90221 | (800) 719-4619 | www.falltech.com

05/17/2024