

PRODUCT SPECIFICATIONS



8242Y3

6' WeldTech® Kevlar® Energy Absorbing Lanyard, Double-leg with Steel Rebar Hooks

Features :

- Features Kevlar® leg webbing throughout
- Includes pliable Soft Pack energy absorber with Nomex® cover.
- Kevlar® webbing delivers excellent burn and spatter resistance
- Includes alloy steel snap hook for harness attachment and rebar hooks for anchorage connections
- Double-leg design facilitates 100% tie-off
- Rebar hooks feature transverse load rated gates
- Complies with ANSI Z359.13-2013



Material Specifications	
Webbing	Kevlar®; 5,000 lb min. static strength
Pack Cover	Tubular Nomex®
Energy Absorber	Polyester tear-away
Connectors	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
Static Strength	5,000 lb min.
ANSI Lanyard Class	6' free fall
Max. Arrest Distance	48"
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
CSA	Z259.11-2017
ANSI	Z359.13-2013
OSHA	1926.502 and 1910.66

Sizes & Part Numbers

8242Y3 (ANSI Compliant)	C8242Y3 (CSA Compliant)
-------------------------------	-------------------------------