

PRODUCT SPECIFICATIONS



82710SC1

10' DuraTech® Web SRL with Steel Snap Hook, Includes Steel Anchorage Carabiner

Features :

- Compact size is simple to install and relocate as worksite changes require
- Dyneema® web lifeline resists abrasion while providing trusted strength.
- Overmolded glass-filled nylon housing contributes unmatched impact resistance
- Internal inertial braking system provides smooth deceleration with minimal fall forces
- Integrated aluminum alloy swivel-eye helps to prevent lifeline twisting for smooth operation
- Features alloy steel snap hook lifeline connector
- Includes alloy steel anchorage carabiner
- Complies with ANSI Z359.14-2014



Material Specifications	
Webbing	Dyneema®/Polyester blend; 4,500 lb min.
Lifeline Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
Static Strength	3,000 lb min.
ANSI SRL Class	Class B
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
Max. Arrest Distance	54"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
ANSI	Z359.14-2014
OSHA	1926.502 and 1910.66
CSA	Z259.2.2-2017

Sizes & Part Numbers

82710SC1 (ANSI Compliant)	C82710SC1 (CSA Compliant)
------------------------------	------------------------------

1306 S. Alameda St., Compton, CA 90221 | (800) 719-4619 | www.falltech.com

05/17/2024