

PRODUCT SPECIFICATIONS



8357Y3

6' ViewPack® Coated Cable Energy Absorbing Lanyard, Double-leg with Steel Connectors

Features :

- Built with rugged 1/4" vinyl-coated galvanized steel cable
- Well-matched for harsh and abrasive environments.
- Energy absorber features patented ViewPack® cover with inspection window
- ViewPack® cover also features WrapPack label protection
- Includes alloy steel snap hook for harness attachment and rebar hooks for anchorage connection
- Double-leg design facilitates 100% tie-off
- Rebar hooks feature transverse load rated gates
- Complies with ANSI Z359.13-2013



Material Specifications	
Cable	Coated galvanized steel; 5,000 lb min. static strength
Energy Absorber	Polyester tear-away
Connectors	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
Static Strength	5,000 lb min.
ANSI Lanyard Class	6' free fall
Max. Arrest Distance	48"
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
OSHA	1926.502 and 1910.66
ANSI	Z359.13-2013